



SOFT BOARD



IBS **SOFTBOARD** is a multi layered softboard used as thermal and sound insulation and underlay for various types of flooring and office partitions. This product has many purposes for both the home and the office.



The mark of responsible forestry

www.ibs.co.nz



SOFT BOARD

Standard Softboards has been produced for over 50 years and is now a key building product internationally. In the past Softboard has been used in wooden construction, traditionally as an insulation.

As a sustainable building material, wood is known for its excellent qualities, both thermal and ecological. IBS Softboard is easy to handle, non-allergenic and very durable, providing long-term performance.

APPLICATIONS

- Thermal and Sound Insulation
- Underlay for different types of floors
- Pinboards and Displays
- Office Partitions
- Sound Deadening Doors

SIZE:

1220X2440X12MM



IBS SOFTBOARD TECHNICAL INFORMATION

- Produced according to EN 13986 and EN 13171
- Fire Class Rating according to EN13501-1 E
- Thermal Conductivity Factor = 0.048 W/m.K
- Water Vapour Diffusion = 5
- Specific Heat Capacity 2100 J/kgK
- Density 230 kg/m³
- Tensile Strength ≥ 10
- Compression strength ≥ 100 KPa

STORAGE AND TRANSPORT

- Store flat in a dry place
- Protect edges from damage
- Carry single board vertically
- Cut with insulation knife or hand circular saw with dust collector
- Avoid cross cuts